

外置输入/输出模块



Sedomat 控制器特別為自動化控制器而沒有內置輸入/出點的控制器提供週邊外置輸入/出接線盒PROFIBUS DP. 包括數字及模擬輸入和輸出.

Profi 16 及Profi 32 特別設計用於紡織染整機械，並能融合其他機械供應商的模塊.

优化纺织整理工序

接線盒

ProfibusDP接線盒
是世界公認標準通
訊輸入/輸出裝置連
接線用



於變頻器, PLC組合件, 感應器, 閥
門, 遙距顯示, 等等.

標準工業用通訊已經被策略性地選用
為公開連接. 的一部份.

地域通訊概念能有效地減低建築物的
電柜大量佈線. 眾多週邊PROFIBUS
DP 接線盒為不同組合件提供配套.
同時為不同價格凡機台提供靈活性
選擇.

ProfibusDP接線盒地域被下列供應商
支援. Siemens, Klockner Moeller,
Mitsubishi,

Matsushita, Allen- Bradley,
Omron, Weidmuller, Wago, Lenz,
KEB, Hitachi, Festo, Parker,
etc.

概念:

- 所有輸入點設定為綠色二極管, 輸
出點設定為紅色二極管.
- 所有輸入及輸出點均是光電學運作
- 4只二極管顯示實時狀態.
- 所有連接線均設插入接點.
- Profibus 連接線長度隨意選定

規格:

輸入點:

- 2 analog inputs
- 0-20 mA 或 4-20 mA.
- 2 PT-100 溫度輸入點.
- 0- 150° C.
- 16 (32用於Profi 32) 數字輸入.
- 2計算器 800 Hz

輸出點:

- 4 模擬輸出點
- 0-20 mA 或 4-20 mA.
- 16 (32用於Profi 32) 數字輸出
(最高 0.5 A /輸出)

地域通訊:

Profibus DP 從屬.

供電:

24 VDC (19-32V)

Profi 16 尺寸:

243.3 x 133 x 54.6 mm (闊x高x長)

Profi 32 尺寸:

359.9 x 133 x 54.6 mm (闊x高x長)

Head office:

Sedo Treepoint GmbH, Germany
Neuwies 1, D-35794 Mengerskirchen
Phone: + 49 6476 31-0, Fax: +49 6476 31-31
sedo@sedo-treepoint.com

Sedo Treepoint, Switzerland
Phone: + 41 43 488 11 88, Fax: +41 43 488 11 89
switzerland@sedo-treepoint.com

Sedo Treepoint, Belgium
belgium@sedo-treepoint.com

Sedo Treepoint, Italy
italy@sedo-treepoint.com

Sedo Treepoint, UK
uk@sedo-treepoint.com

Sedo Treepoint, USA
usa@sedo-treepoint.com

Sedo Treepoint, India
india@sedo-treepoint.com

Sedo Treepoint, Singapore
singapore@sedo-treepoint.com

(中文翻译, 如有错漏, 以原文为准)

Technical specifications are subject to change without prior notice.