

Cost-effective controller for a high degree automation

SedoTreepoint		SEDOMAT 6007	
((\))			

fo

Designed for the Smart Factory

The Sedomat 6007 is a cost-effective solution for a high degree automation specially designed to meet the requirements of Industry 4.0. It comes with a user-friendly 7" touch display and is equipped with Modbus RTU (RS232). It already includes a PLC which can be adapted with programming tools and can be optionally equipped with internal and external I/O boards to meet the different requirements of yarn, fabric and other types of dyeing machines.

A more sustainable competitive production can be realized due to the integration of SedoMaster and other dye house systems via Ethernet, OPC UA and MQTT interfaces. Also, data acquisition or the use of Sedomat 6007 as production client is possible by optional RFID support.

Like all Sedo Treepoint controllers the Sedomat 6007 guarantees high quality and reliability in rugged production environments.



Sedomal 6007

Internal I/O board options

- Embedded internal I/O board IO16/2 with 16 digital I/Os, 4 software counters (4 kHz), 2 hardware counters (10 kHz), 2 analog inputs, 2 analog outputs
- Internal I/O board 32/6 with 32 digital I/Os, 4 software counters (4 kHz), 4 hardware counters (10 kHz), 6 analog inputs, 6 analog outputs

Specifications		Sedomał 6007
Capacitive touch display		7"
Bus systems (Master)	CANopen [®]	-
	PROFIBUS DP®*	-
	Modbus RTU (RS232/485)	✓
	Modbus TCP	\checkmark
Internal I/O boards	I/O board IO16/2*	1
	I/O board 1032/6*	1
0	Internal modules*	2
SedolO	External modules*	1
Internal I/O boards	RS232 interface	\checkmark
internal i/o boarus	RS485 interface	\checkmark
Ethernet (RJ45), 1 GBit/s		1
USB 2.0 port / USB 3.1 port		-/1
Wi-Fi		-
OpenVPN Client		\checkmark
OPC UA Server, MQTT Server		\checkmark
RFID reader*		\checkmark
mPCle slot		-
mSATA slot		-
IP67 protection		\checkmark
Power supply 24 V DC, 1.0 A		\checkmark
Ambient temperature 0 - 60 °C (32 - 140 °F)		\checkmark
Dimensions (wxhxd)		285 x 216 x 65 mm
Panel cut-out (wxh)		270 x 196 mm ± 1 mm

*Optional configuration, customized to individual needs.



▲ Connections and interfaces Sedomat 600/



Head office: Sedo Treepoint GmbH, Germany Neuwies 1, D-35794 Mengerskirchen Phone: + 49 6476 31-0 sedo@sedo-treepoint.com

> Sedo Treepoint, Switzerland switzerland@sedo-treepoint.com Sedo Treepoint, Belgium belgium@sedo-treepoint.com Sedo Treepoint, China china@sedo-treepoint, India india@sedo-treepoint, India sedo Treepoint, Singapore singapore@sedo-treepoint.com

> > Sedo Treepoint, USA usa@sedo-treepoint.com

Technical specifications are subject to change without prior notice.